

Variable Ratio, Enclosed, Positive Displacement Meter



**Servo-Flo 605 Enclosed
Variable Ratio Meter System
with 5 Gallon A and B Supply Pumps**

- ▶ **Dual independent meter cylinders allow selection of any material ratio setting**
- ▶ **Dual servo motor drive motors maintains preset fluid ratio and desired flow rate**
- ▶ **Positive Rod Displacement metering technology for precision dispensing**
- ▶ **Flow rate is variable during the dispense cycle while maintaining ratio specification**
- ▶ **Designed for low to high viscosity unfilled and abrasive filled materials**
- ▶ **Designed for low and high flow rates**
- ▶ **Includes wear resistant wetted components and long life seals**
- ▶ **Wide selection of ratio ranges**
- ▶ **Wide selection of volume ranges**
- ▶ **Able to dispense varying shot sizes throughout the dispense cycle**
- ▶ **See Servo-Flo 105 for floor or portable cart mount systems**

Dual Servo Drive Meter Mix Dispense System for Adhesive and Sealant Materials

Servo-Flo 605 efficiently dispenses 2-component materials in high volume production or manual application environments. It's ideal for applications demanding precision volumetric shot or bead profile dispensing of low to high viscosity or viscous and abrasive materials.

The material is supplied by low or high pressure supply pumps or pressure tanks.

The meter delivers on-ratio material to a wide variety of automatic or manual 2-component fluid dispense valves.

Typical Applications

- Shot dispense applications
- Bead profile dispensing
- Electronic potting applications
- Different shot volumes per part
- Automated dispensing applications
- Robotic dispensing processes
- Manual dispensing applications

Servo-Flo[®] 605 - Variable Ratio Meter



Features:

- Enclosed cabinet meter system
- Configured for abrasive and heated materials
- Optional water heat/cool or electrically heated material temperature control
- Optional material filters available
- Meter accepts supply pumps or pressure tanks
- Variable hose lengths to automatic or manual 2-component mix and dispense valve
- Optional foot pedal dispense control

Specifications:

- Up to 16 cc volume at 1:1 volumetric ratio
- 230 VAC power supply recommended
- Up to 34 cc/second flow rate at 1:1 ratio
- Supply Pump or Pressure Tank material supply
- Compatible seal materials are selected at order



Servo-Flo 605 shown with 5 Gallon Pressure Supply Tanks and Foot Pedal Dispense Start Control

3 Levels of Operator Interface Controls:

Basic Series interface screen
Intermediate Series interface screen (shown)
Automotive Series interface screen



Manufacturers of Precision Dispense Systems & Valves

45677 Helm Street • P.O. Box 701460
Plymouth, MI 48170 • USA
Phone: (734) 459-8600 Fax: (734) 459-8686
Web: www.SealantEquipment.com
E-mail: sales@SealantEquipment.com